

Protector Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Large 2-person fold down handles
- Watertight, crushproof, and dustproof
- Open cell core with solid wall design - strong, light weight
- 3 level Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Peli's legendary lifetime guarantee\*\*
- O-ring seal
- \* Where applicable by law
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 24.00 x 24.00 x 24.00 in |
| Interior (L×W×D) - Centimeters | 60.96 x 60.96 x 60.96 cm |
| Exterior (L×W×D) - Inches      | 26.50 x 26.50 x 25.25 in |
| Exterior (L×W×D) - Centimeters | 67.31 x 67.31 x 64.14 cm |
| Padlock Hole Diameter          | 0.31 in                  |

CAPACITY

|              |                     |
|--------------|---------------------|
| Lid Depth    | 5.00 in (12.7 cm)   |
| Bottom Depth | 19.00 in (48.26 cm) |
| Buoyancy     | 465.18 lbs          |

WEIGHTS

|                    |                      |
|--------------------|----------------------|
| Weight With Foam   | 41.00 lbs (18.6 kg)  |
| Weight No Foam     | 31.97 lbs (14.5 kg)  |
| Master Pack Weight | 46.78 lbs (21.22 kg) |
| Weight             | 45.4 lbs (20.59 kg)  |

TEMPERATURE RANGE

|                     |                |
|---------------------|----------------|
| Minimum Temperature | -40°F (-40°C)  |
| Maximum Temperature | 190°F (87.8°C) |

MATERIALS

|                       |                                |
|-----------------------|--------------------------------|
| Body Material         | Polypropylene                  |
| Latch Material        | ABS                            |
| O Ring Material       | Polymer                        |
| Pins Material         | Stainless Steel                |
| Foam Material         | 1.3 lb Polyurethane            |
| Purge Body Material   | ABS                            |
| Purge Vent Material   | 3 Micron Hydrophobic Non-Woven |
| Purge O Ring Material | 70 Shore Nitrile               |