

With over 11 cubic feet (0.311 cubic meters) of space, you can store, protect, and move large loads in seconds. The reinforced honeycomb deck and lid construction provide support for heavy equipment, or multiple stacking on a 463L pallet. Opening the case at any altitude is not a problem- the dual integrated automatic pressure equalization valves keep moisture out and prevent vacuum lock, and the double wide grip makes lifting easy. With an IP55 certification, the 0550 Transport Case will protect your gear against rain and dirt. The 0550 Transport Case: Built to move-by forklift, by wheel, by hand.

- Fit six 0550 Cases per 463L military pallet, 18 when stacked!
- Over 11ft3 (.311m3) of storage space
- Four extra-deep base-to-lid locking cleats ensure maximum stacking stability
- Built to move: by forklift, by wheel or by hand
- Open cell core with solid wall design - strong, light weight
- Store documents outside the case with our Document Container
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law
- Locking metal Lidstays keep lid locked in open position
- Reinforced honeycomb deck and lid for added strength
- Dual Integrated Automatic Pressure Equalization Valves
- O-ring seal for dust and water resistant seal (IP55)
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	47.57 x 24.07 x 17.68 in
Interior (L×W×D) - Centimeters	120.83 x 61.14 x 44.91 cm
Exterior (L×W×D) - Inches	51.05 x 27.54 x 22.79 in
Exterior (L×W×D) - Centimeters	129.67 x 69.95 x 57.89 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	3.19 in (8.1 cm)
Bottom Depth	14.49 in (36.8 cm)
Buoyancy	820.00 lbs

WEIGHTS

Weight With Foam	95.00 lbs (43.09 kg)
Weight No Foam	79.20 lbs (35.92 kg)
Master Pack Weight	95.00 lbs (43.09 kg)
Weight	100.5 lbs (45.59 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	ABS
O Ring Material	Polymer
Pins Material	Stainless Steel
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile