

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Fits notebook computers up to 14.4" x 11.1" x 1.7" (36.58 x 28.19 x 4.32 cm)
- \* Check with your airline for exact measurement requirements.
- 2 in 1 protection: detachable computer sleeve and accessories pouch
- Maximum airline carry on size\*
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Easy open double-throw latches
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Comfortable rubber over-molded top and side handles
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law

## SPECS

### MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 19.75 x 11.00 x 7.60 in  |
| Interior (L×W×D) - Centimeters | 50.17 x 27.94 x 19.3 cm  |
| Exterior (L×W×D) - Inches      | 22.00 x 13.81 x 9.00 in  |
| Exterior (L×W×D) - Centimeters | 55.88 x 35.08 x 22.86 cm |
| Padlock Hole Diameter          | 5/16 in                  |

### CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 1.79 in (4.55 cm)  |
| Bottom Depth | 5.79 in (14.71 cm) |
| Buoyancy     | 64.15 lbs          |

WEIGHTS

|                    |                      |
|--------------------|----------------------|
| Weight With Foam   | 13.60 lbs (6.17 kg)  |
| Weight No Foam     | 11.99 lbs (5.44 kg)  |
| Master Pack Weight | 32.43 lbs (14.71 kg) |
| Weight             | 15.6 lbs (7.08 kg)   |

TEMPERATURE RANGE

|                     |                |
|---------------------|----------------|
| Minimum Temperature | -40°F (-40°C)  |
| Maximum Temperature | 190°F (87.8°C) |

MATERIALS

|                       |                                |
|-----------------------|--------------------------------|
| Body Material         | Polypropylene                  |
| Latch Material        | ABS                            |
| O Ring Material       | Polymer                        |
| Pins Material         | Stainless Steel                |
| Foam Material         | 1.3 lb Polyurethane            |
| Purge Body Material   | ABS                            |
| Purge Vent Material   | 3 Micron Hydrophobic Non-Woven |
| Purge O Ring Material | 70 Shore Nitrile               |