

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Fit two 0500 Cases per pallet, four when stacked!
- Store documents outside the case with our Document Container
- Can be inverted and used as a pallet with an airtight cover
- Watertight, crushproof, and dustproof
- Open cell core with solid wall design - strong, light weight
- Double wide grip fold down handles - makes lifting easy
- Easy open double-throw latches
- Dual Integrated Automatic Pressure Equalization Valves
- Lid is completely removable
- Peli's legendary lifetime guarantee**
- O-ring seal
- * Where applicable by law
- Optional Caster Wheel Kit complete with brakes
- Optional Pallet Riser Kit
- Lifetime Guarantee of Excellence

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	34.95 x 18.45 x 25.25 in
Interior (L×W×D) - Centimeters	88.77 x 46.86 x 64.14 cm
Exterior (L×W×D) - Inches	39.95 x 23.45 x 28.65 in
Exterior (L×W×D) - Centimeters	101.47 x 59.56 x 72.77 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	2.25 in (5.72 cm)
Bottom Depth	23.00 in (58.42 cm)
Buoyancy	780.00 lbs

WEIGHTS

Weight With Foam	58.60 lbs (26.58 kg)
Weight No Foam	50.00 lbs (22.68 kg)
Master Pack Weight	69.00 lbs (31.3 kg)
Weight	70.2 lbs (31.84 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	EXL
O Ring Material	Polymer
Pins Material	Stainless Steel
Foam Material	1.3 lb Polyurethane
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile