

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings
- Water resistant, crushproof, and dust resistant
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Fold down handles
- Easy open double-throw latches
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Personalized nameplate service available

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	21.78 x 16.69 x 10.62 in
Interior (L×W×D) - Centimeters	55.32 x 42.39 x 26.97 cm
Exterior (L×W×D) - Inches	26.20 x 23.00 x 13.68 in
Exterior (L×W×D) - Centimeters	66.55 x 58.42 x 34.75 cm
Padlock Hole Diameter	5/16 in

CAPACITY

Lid Depth	2.05 in (5.21 cm)
Bottom Depth	8.57 in (21.77 cm)

WEIGHTS

Weight With Foam	29.10 lbs (13.2 kg)
Weight No Foam	26.30 lbs (11.93 kg)
Weight	35.7 lbs (16.19 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	ABS
O Ring Material	Polymer
Pins Material	Stainless Steel
Foam Material	1.3 lb Polyurethane
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile