

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Watertight, crushproof, and dustproof
- 5-piece foam set
- Easy open double-throw latches
- Fold down handles
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- O-ring seal
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Personalized nameplate service available

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	34.00 x 24.00 x 12.50 in
Interior (L×W×D) - Centimeters	86.36 x 60.96 x 31.75 cm
Exterior (L×W×D) - Inches	37.50 x 27.13 x 14.37 in
Exterior (L×W×D) - Centimeters	95.25 x 68.91 x 36.5 cm
Padlock Hole Diameter	0.31 in

CAPACITY

Lid Depth	2.50 in (6.35 cm)
Bottom Depth	10.00 in (25.4 cm)
Buoyancy	416.00 lbs

WEIGHTS

Weight With Foam	38.00 lbs (17.24 kg)
Weight No Foam	30.00 lbs (13.61 kg)
Master Pack Weight	43.00 lbs (19.5 kg)
Weight	43.8 lbs (19.87 kg)

TEMPERATURE RANGE

Minimum Temperature	-40°F (-40°C)
Maximum Temperature	190°F (87.8°C)

MATERIALS

Body Material	Polypropylene
Latch Material	ABS
O Ring Material	Polymer
Pins Material	Stainless Steel
Foam Material	1.3 lb Polyurethane
Purge Body Material	ABS
Purge Vent Material	3 Micron Hydrophobic Non-Woven
Purge O Ring Material	70 Shore Nitrile