

The Pelican™ Storm Case™ has the same legendary DNA as our Pelican Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch.

Guaranteed for life, the Pelican Storm case is made in the USA and engineered using the finest components.

- Five Press & Pull Latches
- Two Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- Powerful Hinges
- O-ring seal
- Guaranteed For Life

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	29.00 x 18.00 x 10.50 in
Interior (L×W×D) - Centimeters	73.66 x 45.72 x 26.67 cm
Exterior (L×W×D) - Inches	31.30 x 20.40 x 12.20 in
Exterior (L×W×D) - Centimeters	79.5 x 51.82 x 30.99 cm
Padlock Hole Diameter	0.28 in

CAPACITY

Lid Depth	2.00 in (5.08 cm)
Bottom Depth	8.50 in (21.59 cm)
Buoyancy	200.85 lbs

WEIGHTS

Weight With Foam	28.70 lbs (13.02 kg)
Weight No Foam	20.80 lbs (9.43 kg)
Master Pack Weight	28.00 lbs (12.7 kg)

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	Injection Molded HPX™ high performance resin
Latch Material	Valox - Polybutylene Terephthalate (PBT)
Latch Alt Material	Xenoy - Polyester/Polycarbonate blend
O Ring Material	EPDM
Pins Material	Stainless Steel
Pins Alt Material	Aluminum
Foam Material	1.3/1.35 polyester
Purge Body Material	Valox - Polybutylene Terephthalate (PBT)
Purge Body Alt Material	Xenoy - Polyester/Polycarbonate blend
Purge Vent Material	Gortex membrane
Purge O Ring Material	Buna-N, 50-60 Durometer Shore A