

AL2423-0911AC-HL



Pelican Hardigg

- One-piece construction, molded from lightweight, high-impact polyethylene
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Recessed hardware for extra protection

AL2423-0911AC-HL

SPECS

MEASUREMENTS

Interior (L×W×D) - Inches	24.75 x 23.25 x 20.00 in
Interior (L×W×D) - Centimeters	62.87 x 59.06 x 50.8 cm
Exterior (L×W×D) - Inches	27.75 x 26.25 x 23.19 in
Exterior (L×W×D) - Centimeters	70.49 x 66.68 x 58.9 cm

CAPACITY

Lid Depth	11.25 in (28.58 cm)
Bottom Depth	8.75 in (22.23 cm)
Buoyancy	578.52 lbs

WEIGHTS

Weight	31.80 lbs (14.42 kg)
Master Pack Weight	33.80 lbs (15.33 kg)

TEMPERATURE RANGE

Minimum Temperature	-20°F (-28.9°C)
Maximum Temperature	140°F (60°C)

MATERIALS

Body Material	RotoMolded Polyethylene
Hardware Material	Yellow Carbon Steel Standard
Optional Hardware Material	Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black
Handle Material	Heavy Duty Injection Molded Standard
Optional Handles Material	Stainless Steel Passivate and Stainless Steel Black
Latch Material	Steel (Nickel-black Plated)
O Ring Material	Silicone Sponge
Purge Body Material	Aluminum
Prv Valve Material	138
Foam Material	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined