

# AL3019-0709AC-HL



Pelican Hardigg

- One-piece construction, molded from lightweight, high-impact polyethylene
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Recessed hardware for extra protection

AL3019-0709AC-HL

## SPECS

### MEASUREMENTS

|                                |                          |
|--------------------------------|--------------------------|
| Interior (L×W×D) - Inches      | 30.75 x 19.62 x 16.98 in |
| Interior (L×W×D) - Centimeters | 78.11 x 49.83 x 43.13 cm |
| Exterior (L×W×D) - Inches      | 33.75 x 22.62 x 19.67 in |
| Exterior (L×W×D) - Centimeters | 85.73 x 57.45 x 49.96 cm |

### CAPACITY

|              |                    |
|--------------|--------------------|
| Lid Depth    | 9.34 in (23.72 cm) |
| Bottom Depth | 7.64 in (19.41 cm) |
| Buoyancy     | 501.95 lbs         |

### WEIGHTS

|                    |                      |
|--------------------|----------------------|
| Weight             | 40.60 lbs (18.42 kg) |
| Master Pack Weight | 42.60 lbs (19.32 kg) |

### TEMPERATURE RANGE

|                     |                 |
|---------------------|-----------------|
| Minimum Temperature | -20°F (-28.9°C) |
| Maximum Temperature | 140°F (60°C)    |

MATERIALS

|                            |                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------|
| Body Material              | RotoMolded Polyethylene                                                                  |
| Hardware Material          | Yellow Carbon Steel Standard                                                             |
| Optional Hardware Material | Black Carbon Steel, Stainless Steel Passivate and Stainless Steel Black                  |
| Handle Material            | Heavy Duty Injection Molded Standard                                                     |
| Optional Handles Material  | Stainless Steel Passivate and Stainless Steel Black                                      |
| Latch Material             | Steel (Nickel-black Plated)                                                              |
| O Ring Material            | Silicone Sponge                                                                          |
| Purge Body Material        | Aluminum                                                                                 |
| Prv Valve Material         | 138                                                                                      |
| Foam Material              | No Foam, empty case standard<br>Optional PE and PU, 1 and 2 lb. options filled and lined |